



Ref. Certif. No.

JPTUV-157020

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

**CB TEST CERTIFICATE**

Product	EV AC Charger
Name and address of the applicant	Zhejiang Raedian New Energy Technology Co., Ltd No.3, Shuangbai Road, Yuanhua Town, Haining City, 314416 Zhejiang, P.R. China
Name and address of the manufacturer	Zhejiang Raedian New Energy Technology Co., Ltd No.3, Shuangbai Road, Yuanhua Town, Haining City, 314416 Zhejiang, P.R. China
Name and address of the factory	Zhejiang Raedian New Energy Technology Co., Ltd No.3, Shuangbai Road, Yuanhua Town, Haining City, 314416 Zhejiang, P.R. China
Ratings and principal characteristics	Refer to page 2
Trademark (if any)	RAEDIAN
Customer's Testing Facility (CTF) Stage used	N/A
Model / Type Ref.	NORA 7-TH-I-JK-L-MNOP, NORA 7P-TH-I-JK-L-MNOP, NORA 11-TH-I-JK-L-MNOP, NORA 22-TH-I-JK-L-MNOP, NORA 7-S-I-JK-L-MNOP, NORA 7P-S-I-JK-L-MNOP, NORA 22-S-I-JK-L-MNOP (The definition of "TH-I-JK-L-MNOP" and "S-I-JK-L-MNOP" refer to model type definition list for details) Detail information refer to test report CN23HF8J 001
Additional information (if necessary may also be reported on page 2)	
A sample of the product was tested and found to be in conformity with	IEC 61851-1:2017
As shown in the Test Report Ref. No. which forms part of this Certificate	CN23HF8J 001

This CB Test Certificate is issued by the National Certification Body



TÜV Rheinland Japan Ltd.  
Global Technology Assessment Center  
4-25-2 Kita-Yamata, Tsuzuki-ku  
Yokohama 224-0021, Japan  
Phone + 81 45 914-3888  
Fax + 81 45 914-3354  
Mail: info@jpn.tuv.com  
Web : www.tuv.com

Date: 2024-01-31

Signature:

Dipl.-Ing. (FH) Fan He

**Additional information :**

For model NORA 7-TH-I-JK-L-MNOP:  
Input: 230V a.c., 1P+N+PE, 50/60Hz, 32 A a.c.  
Output: 230V a.c., 1P+N+PE, 50/60Hz, 32 A a.c., 7kW  
Operating temperature: -30°C to 50°C  
Protection level: IP65

For model NORA 7P-TH-I-JK-L-MNOP:  
Input: 230V a.c., 1P+N+PE, 50/60Hz, 32 A a.c.  
Output: 230V a.c., 1P+N+PE, 50/60Hz, 32 A a.c., 7kW  
Operating temperature: -30°C to 50°C  
Protection level: IP65

For model NORA 11-TH-I-JK-L-MNOP:  
Input: 400V a.c., 3P+N+PE, 50/60Hz, 16 A a.c.  
Output: 400V a.c., 3P+N+PE, 50/60Hz, 16 A a.c., 11kW  
Operating temperature: -30°C to 50°C  
Protection level: IP65

For model NORA 22-TH-I-JK-L-MNOP:  
Input: 400V a.c., 3P+N+PE, 50/60Hz, 32 A a.c.  
Output: 400V a.c., 3P+N+PE, 50/60Hz, 32 A a.c., 22kW  
Operating temperature: -30°C to 50°C  
Protection level: IP65

For model NORA 7-S-I-JK-L-MNOP:  
Input: 230V a.c., 1P+N+PE, 50/60Hz, 32 A a.c.  
Output: 230V a.c., 1P+N+PE, 50/60Hz, 32 A a.c., 7kW  
Operating temperature: -30°C to 50°C  
Protection level: IP55

For model NORA 7P-S-I-JK-L-MNOP:  
Input: 230V a.c., 1P+N+PE, 50/60Hz, 32 A a.c.  
Output: 230V a.c., 1P+N+PE, 50/60Hz, 32 A a.c., 7kW  
Operating temperature: -30°C to 50°C  
Protection level: IP55

For model NORA 22-S-I-JK-L-MNOP:  
Input: 400V a.c., 3P+N+PE, 50/60Hz, 32 A a.c.  
Output: 400V a.c., 3P+N+PE, 50/60Hz, 32 A a.c., 22kW  
Operating temperature: -30°C to 50°C  
Protection level: IP55

The definition of "TH-I-JK-L-MNOP" and "S-I-JK-L-MNOP" refer to model type definition list for details.